



1FW

PATENT
Customer No. 58,982
New Attorney Docket No. 08350.2476-00000

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:)
Riccardo MARES) Group Art Unit: 3745
Application No.: 10/824,150) Examiner: LOPEZ, FRANK D.
Filed: April 14, 2004) Confirmation No.: 6378
For: SERIES-PARALLEL)
HYDROSTATIC TRANSMISSION)

Mail Stop Issue Fee
Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Sir:

FILING CERTIFIED COPY OF PRIORITY DOCUMENT


This application claims priority to EP 03008650.0, filed April 15, 2003. Please find attached a certified copy of the priority document.

Please grant any extensions of time required to enter this document and charge any additional required fees to our Deposit Account No. 06-0916.

Respectfully submitted,

FINNEGAN, HENDERSON, FARABOW,
GARRETT & DUNNER, L.L.P.

Dated: November 18, 2008

By: 
Panyin A. Hughes
Reg. No. 55,288

Attachment to this Paper includes a Certified Copy of Priority Document EP 03008650.0, filed April 15, 2003.



**Europäisches
Patentamt**

**European
Patent Office**

**Office européen
des brevets**

Bescheinigung

Certificate

Attestation

Die angehefteten Unterlagen stimmen mit der ursprünglich eingereichten Fassung der auf dem nächsten Blatt bezeichneten europäischen Patentanmeldung überein.

The attached documents are exact copies of the European patent application described on the following page, as originally filed.

Les documents fixés à cette attestation sont conformes à la version initialement déposée de la demande de brevet européen spécifiée à la page suivante.

Patentanmeldung Nr. Patent application No. Demande de brevet n°

03008650.8

Der Präsident des Europäischen Patentamts:
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets
p.o.

R C van Dijk



Anmeldung Nr:
Application no.: 03008650.8
Demande no:

Anmeldetag:
Date of filing: 15.04.03
Date de dépôt:

Anmelder/Applicant(s)/Demandeur(s):

BITELLI S.p.A.
Via IV Novembre 2
40061 Minerbio (BO)
ITALIE

Bezeichnung der Erfindung/Title of the invention/Titre de l'invention:
(Falls die Bezeichnung der Erfindung nicht angegeben ist, siehe Beschreibung.
If no title is shown please refer to the description.
Si aucun titre n'est indiqué se référer à la description.)

Smooth pilot-operated series-parallel hydrostatic transmission

In Anspruch genommene Priorität(en) / Priority(ies) claimed /Priorité(s)
revendiquée(s)

Staat/Tag/Aktenzeichen/State/Date/File no./Pays/Date/Numéro de dépôt:

Internationale Patentklassifikation/International Patent Classification/
Classification internationale des brevets:

F16H61/00

Am Anmeldetag benannte Vertragsstaaten/Contracting states designated at date of
filing/Etats contractants désignées lors du dépôt:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LU MC NL
PT RO SE SI SK TR LI

Communication

concerning the registration of amendments relating to

- a transfer (Rules 20 and 61 EPC)
- entries pertaining to the applicant/the proprietor (Rule 92(1)(f) EPC)

As requested, the entries pertaining to the applicant of the above-mentioned European patent application / to the proprietor of the above-mentioned European patent have been amended to the following:

CATERPILLAR PAVING PRODUCTS INC. - Minnesota/US

The registration of the changes has taken effect on 25.01.06

SMOOTH PILOT-OPERATED SERIES-PARALLEL HYDROSTATIC TRANSMISSION

Technical Field

5 The present invention relates to a hydraulic transmission system and a method of operating the same. In particular it relates to a hydraulic transmission system with a closed circuit connection configuration and preferably having at least two motors connected to one hydraulic working fluid
10 supply means.

Background of the Invention

15 Hydraulic transmission systems are widely used in particular in environments where large forces and torques have to be handled. For example, one particular field of application of hydraulic transmission systems is self propelled or mobile working machines, such as construction machines or load lifting machines. Typically, in one such hydraulic transmission system, two or more motors may be connected in parallel to one hydraulic working fluid
20 supply. Further, in case a variable displacement pump is employed as the hydraulic working fluid supply, a high motor torque can be achieved from a relatively small displacement pump, which is important in mobile working machines where space is limited.

25 In hydraulically operated working systems the flow of hydraulic working fluid supplied to the motors may be controlled either by a hydraulic or by an electronic control or by combinations thereof. This offers flexibility in designing the system according to the specific needs. For example, in a hydraulic system with parallel connected motors in which the flow of hydraulic working
30 fluid in the individual branches is governed by the load on the motors, problems may arise in case one of the motors is not sufficiently loaded and the flow resistance of this transmission branch gets so low that nearly all the hydraulic working fluid supplied by the displacement pump flows through this

branch. This may cause "slippage" of the respective motor and the other motor(s) will not receive enough hydraulic working fluid. Attempts to avoid such a situation include the regulation of flow in the individual branches that is controlled hydraulically and/or electronically. One prior art approach is to use
5 flow dividers that split the flow supplied from a pump in predetermined portions at any time. This, however, causes extra pressure drop or resistance in the hydraulic transmission system and increases the overall costs. Further, in most systems, variable displacement pumps are used and also the available flow of the working fluid supply may be controlled according to the
10 specific need and instant load of the system hydraulically and/or electronically so as to achieve optimum performance of the whole system. Yet, often the results leave room for improvements in particular concerning the reduction of complexity while achieving, at the same time, accurate smooth control of the hydraulic system and its components.

15

Summary of the Invention

According to the present invention an improved hydraulic transmission system is provide which comprises: supply means adapted to supply a variable flow
20 rate of hydraulic working fluid, said supply means comprising hydraulic adjustment means for adjusting the variable flow rate of the hydraulic working fluid; actuatable hydraulic control means having an actuated condition in which the actuatable hydraulic control means generates a hydraulic control fluid having a control pressure which is adjustable between an initial control
25 pressure and a maximum control pressure; and first connection control means operable by said hydraulic control fluid supplied from said hydraulic control means and adapted to direct, upon actuation of said hydraulic control means, said hydraulic control fluid to said hydraulic adjustment means. According to the improved hydraulic transmission system the supply means can be
30 accurately and smoothly adjusted while greatly reducing the complexity and costs of the system.

Further, the present invention provides for an improved hydraulic transmission system comprising: supply means adapted to supply hydraulic working fluid at variable pressure to at least two working lines; at least two hydraulic users connected to said supply means via said at least two working lines in a closed circuit configuration; control means generating a control signal indicative of a desired flow rate of the hydraulic working fluid supplied by said supply means; and second connection control means responsive to said control signal adapted to control the connection of working line portions connected to the at least two users so as to selectively provide serial and/or parallel connection of the at least two hydraulic users depending on said control signal. Thus, the connection configuration can be controlled so as to avoid slippage of one of the motors in the improved hydraulic system.

The invention also provides for a method for controlling a hydraulic transmission system, wherein said hydraulic transmission system comprises supply means for supplying hydraulic working fluid at variable flow rate and wherein said supply means comprises hydraulic adjustment means for adjusting the variable flow rate of the hydraulic working fluid. The method comprises the steps of: providing a hydraulic control fluid having a control pressure which is adjustable between an initial control pressure and a maximum control pressure, said control pressure being indicative of a desired flow rate of the hydraulic working fluid; selectively directing said hydraulic control fluid during an actuated condition to said hydraulic adjustment means, and operating said hydraulic adjustment means by means of said hydraulic control fluid.

Finally, the present invention also provides for a method of controlling a hydraulic transmission system which comprises supply means adapted to supply hydraulic working fluid at variable flow rate to at least two working lines, and at least two hydraulic users connected to said supply means via said at least two working lines in a closed circuit configuration. The method comprises the steps of: providing a control signal indicative of a desired flow rate of the hydraulic working fluid supplied by said supply means; controlling

the connection of working line portions connected to the at least two users so as to selectively provide serial and/or parallel connection of the at least two hydraulic users in response to said control signal.

5 **Brief description of the Drawings**

Further objects, features and advantages of the present invention will become apparent to those skilled in the art upon reading the following description of embodiments of the invention in conjunction with the appended drawings, in
10 which:

Fig. 1 shows a schematic representation of an embodiment of a hydraulic system;

Fig. 2 shows a detail of the hydraulic system of Fig. 1;

15 Fig. 3 shows a schematic representation of the hydraulic system of Fig. 1 in another condition;

Fig. 4 shows the detail of Fig. 2 in the condition of the hydraulic system as shown in Fig. 3;

20 Fig. 5 shows a diagram representing a motor and pump flow rate in the system of Fig. 1.

Detailed Description

Fig. 1 shows a schematic representation of a hydraulic system 1 used in a
25 machine which may be a working machine with hydraulically driven implements such as, for example, but not restricted thereto, a compactor or asphalt roller, a skids steer loader, a hydraulic winch, a construction machine as a paver or a road scarifier with hydraulic implements and traction system, such as hydraulically driven wheels or tracks, or any other utility machine.

30

The hydraulic system 1 of the preferred embodiment constitutes a closed circuit connection and comprises a supply means 3 supplying a variable flow of hydraulic working fluid at first and second supply ports 5, 7 to first and

second working lines 9, 11. The hydraulic system 1 also comprises a first motor or user 13 and a second motor or user 15 both being connected to the supply means 3 via the first and second working lines 9, 11, respectively. Just for reasons of explanation, the first and second motors 13, 15 may be used to drive front and rear rollers of an asphalt roller. They may be also used for driving left and right wheels of, for example, a front and/or rear axle of any self-propelled utility machine or for controlling the operation of any other working implement such as a bucket of an excavator or a conveyor means in a construction machine etc. It is also clear, that more than two motors may be provided depending on the particular use of the hydraulic system 1. The circuit of the hydraulic system 1 comprising the supply means 3 and the first and second motors 13, 15 is closed via first, second, third, and fourth working line portions 21, 23, 25, 27 which are connectable via ports provided on a connection control device 29.

The hydraulic system 1 further comprises a remote control means 31 for facilitating manual remote control of the operation of the supply means 3 and hence the operation of the first and second motors 13, 15. The remote control means 31 is actuatable by the operator of the machine comprising the hydraulic transmission system and has a control lever or joy stick 33 which is manipulated by the operator, for example, to drive the machine at a desired speed in the forward or in the rearward direction. In the preferred embodiment, the actuatable remote control means 31 is of the hydraulic type that includes a pressure variation means 35. Upon manipulating the joystick 33, the pressure variation means 35 of the hydraulic remote control means 31 vary the pressure of a hydraulic control fluid which is introduced at a constant pressure into the hydraulic remote control means 31 via a constant pressure inlet port 37. The hydraulic control fluid with varied pressure is output from the hydraulic remote control means 31 via either a first control output port 39, e.g. for forward drive, or a second control output port 41, e.g. for rearward drive in the above example of an asphalt roller. In the preferred embodiment, the modulated or varied pressure may range from 5 to 20 bar, for example, but

any pressure range suited to the particular application of the hydraulic system 1 can be readily substituted.

5 The first and second control output ports 39, 41 are connected to first and second remote control input ports 43, 45 of the supply means 3 via first and second remote control lines 47, 49, respectively, to control operation of the supply means 3.

10 The supply means 3 comprises a variable displacement pump 51 which is illustrated in the preferred embodiment as a pump of the axial piston type with swash plate design driven via an input shaft 53 by means of a prime mover or engine not shown. The variable displacement pump 51 may be also of another design suitable to supply the hydraulic working fluid at variable flow rate. The pump 51 is connected to the first and second supply ports 5, 7 of the supply means 3 via first and second internal connection lines 55, 57. The supply means 3 also comprises first and second relief valves 59, 61 provided in an internal connection branch parallel to the first and second supply ports 5, 7 between the first and second internal connection lines 55, 57. Said first and second relief valves 59, 61 protect the hydraulic system 1 against overpressure and prevent overloading of the motors 13, 15, as is known in the art.

25 Further, as is well known in the art, there is provided an auxiliary or boost pump 63 which serves to supply boost hydraulic fluid to the variable displacement pump 51 and hydraulic fluid at constant pressure, for example at 20 bar, for control purposes in the hydraulic system 1. The auxiliary pump 63 is connected to a hydraulic fluid tank 65 via a hydraulic fluid supply line 67 and a hydraulic fluid suction port 69 being provided with a filter. The pressure of the hydraulic fluid supplied by the auxiliary pump 63 is limited by a third relief valve 71 connected to an outlet of the auxiliary pump 63 and the hydraulic fluid tank 65, as is known in the art. The outlet of the auxiliary pump 63 is also connected via an internal constant pressure line 73 to a constant pressure output port 75 of the supply means 3.

The variable displacement pump 51 comprises an adjustment means 77 for controlling the output flow of the pump 51, for example by adjusting the angle of the swash plate of the axial piston pump with swash plate design. In a preferred embodiment, the adjustment means 77 is an hydraulic adjustment means and comprises, for example, a double acting servo piston 79 having its two piston chambers connected to first and second servo piston control lines 81, 83. The first and second servo piston control lines 81, 83 are internally connected to first and second constant pressure inlet ports 85, 87 of the supply means 3 and they are also internally connected to a distributor means 89. The adjustment means 77 are operated by the pressure or flow of hydraulic fluid supplied to the piston chambers of the servo piston 79 via the first and second servo piston control lines 81, 83 from the distributor means 89 and the first and second constant pressure inlet ports 85 and 87 as will be described in more detail below.

In particular, the distributor means 89 comprises a directional distributor valve 91 which has a neutral position 93 as represented in Fig. 1, and a first and second control position 95, 97 in which either the first or the second servo piston control lines 81, 83 are connected selectively to an internal servo pressure supply line 99 so as to supply pressurized hydraulic fluid to the piston chambers of the servo piston 79 to control the position thereof. In the neutral position 93 the directional distributor valve 91 connects the first and second servo piston control lines 81, 83 and the first and second constant pressure inlet ports 85, 87 to the hydraulic fluid reservoir or tank 65 in order to balance the neutral position of the servo piston 79. As will be described later, the constant pressure present at the inlet ports 85, 87 in the neutral position 93 of the distributor valve 91 is the constant pressure supplied by the auxiliary pump 63.

Contrary to conventional design in which the distributor valve 91 connects in its first or second control position 93, 95 the first and second servo piston control lines 81, 83, respectively, to the constant pressure hydraulic fluid

present at the outlet of the auxiliary pump 63 to receive the full boost or charge pressure thereof, a conventional connection between the auxiliary pump 63 and the distributor valve 91 is indicated as being blocked by a plug 101. Instead, the internal servo pressure supply line 99 is connected to a
5 servo pressure inlet port 103 of the supply means 3 receiving a pressure or flow of hydraulic fluid which is controlled in a manner to be described later.

The distributor valve 91 may be a proportional valve and it is pilot operated. Thus, its position is controlled by a pilot or control signal for example in the
10 form of pressurized fluid received via first and second distributor pilot lines 105, 107 which are connected to the first and second remote control input ports 43, 45, respectively. As indicated in Fig. 1, the distributor valve 91 also has a swash plate feedback 109, as is known in the art.

15 The first and second remote control input ports 43, 45, the constant pressure output port 75, the first and second constant pressure input ports 85, 87, and the servo pressure inlet port 103 of the supply means 3 are connected to a first control portion 121 of the connection control device 29 adapted to selectively connect or disconnect hydraulic fluid having a constant pressure as
20 supplied from the auxiliary pump 63 and the hydraulic control fluid having a varied pressure as supplied from either the first or the second control output ports 39, 41 of the hydraulic remote control means 31. In other words, the hydraulic transmission system 1 comprises a first connection control means 122 adapted to direct hydraulic control fluid from the hydraulic remote control
25 means 31 to the hydraulic adjustment means 77 of the variable displacement pump 51, said first connection control means 122 comprising the distributor means 89 and the first control portion 121 of the connection control device 29.

Specifically, the constant pressure output port 75 of the supply means 3 is
30 connected via a first external constant pressure supply line 123 to a first input port 125 of the first control portion 121. The first and second constant pressure input ports 85, 87 of the supply means 3 are connected via second and third external constant pressure supply lines 127, 129 to first and second

output ports 131, 133 of the first control portion 121. The servo pressure inlet port 103 of the supply means 3 is connected via an external servo pressure supply line 135 to a third output port 137 of the first control portion 121.

5 As mentioned previously, the first and second remote control input ports 43, 45 are connected via the first and second remote control lines 47, 49 to the first and second remote control output ports 39, 41, respectively, of the hydraulic remote control means 31. In particular, both the first and second remote control lines 47, 49 are connected to the first and second remote
10 control input ports 43, 45 via the connection control device 29 and comprise respective first external line portions 139, 141 connecting the first and second remote control output ports 39, 41 with second and third input ports 143, 145 of the connection control device 29. Further, they comprise second line portions 147, 149 internal to the connection control device 29 and connecting
15 the second and third input ports 143, 145 with fourth and fifth output ports 151, 153 of the connection control device 29. Finally there are provided third external line portions 155, 157 of the first and second remote control lines 47, 49 connecting the fourth and fifth output ports 151, 153 with the first and second remote control input ports 43, 45 of the supply means 3.

20 The first control portion 121 of the connection control device 29 also comprises a sixth output port 159 internally connected to the first input port 125 of the connection control device 29 and providing hydraulic fluid with the constant pressure of the auxiliary pump 63. The sixth output port 159 is
25 connected via a fourth external constant pressure supply line 161 to the constant pressure inlet port 37 of the hydraulic remote control means 31.

The first control portion 121 of the connection control device 29 has a first
30 switching means 171 adapted to selectively supply the hydraulic fluid with constant pressure from the auxiliary pump 63 to the first and second output ports 131, 133. In other words, the first switching means 171 is adapted to connect and disconnect the first and second output ports 131, 133 of the first control portion 121 to and from the auxiliary pump 63.

Referring to an enlarged schematic representation of the connection control device 29 in Fig. 2, the first control portion 121 comprises a first internal connection line 175 connecting the first input port 125 to the first switching means 171 and, as mentioned above, to the sixth output port 159. The first switching means 171 is also connected to a second internal connection line 177 which is selectively connectable to one of the second or third inputs 143, 145 of the connection control device 29 to receive hydraulic control fluid varied in pressure and as output from one of the first and second control output ports 39, 41 of the hydraulic remote control means 31, as will be described later. The first switching means 171 is further connected to the first and second output ports 131, 133 via a third internal connection line 179 which is bifurcated. Finally there is provided a fourth internal connection line 181 connecting the first switching means 171 with the third output port 137.

15

The switching means 171 of the preferred embodiment comprises an on-off directional valve 183 which has a neutral position 185 (see Figs. 1 and 2) in which the first internal connection line 175 is connected to the third internal connection line 179. Thus, in the neutral position 185 of the on-off directional valve 183, the hydraulic fluid having constant pressure of the auxiliary pump 63 is applied to the first and second output ports 131, 133 of the connection control means 29 and, therefore, also to the first and second constant pressure inlet ports 85, 87 of the supply means 3.

20

The on-off directional valve 183 has also an activated position 187 in which it connects the second internal connection line 177 to the fourth internal connection line 181 to supply the hydraulic fluid varied in pressure from one of the first and second control output ports 39, 41 of the hydraulic remote control means 31 to the servo pressure inlet port 103 of the supply means 3. In the activated position 187, the first and second output ports 131, 133 are disconnected from the constant pressure supply of the first input port 125. On the other hand, in the neutral position 185, the third output port 137 is disconnected from the hydraulic fluid as supplied from either one of the first

30

and second control output ports 39, 41 of the hydraulic remote control means 31.

5 Preferably the on-off directional valve 183 is pilot operated and connected to a first internal pilot line 189 which is selectively connectable via a second switching means 191 of the connection control device 29 to one of the first and second control output ports 39, 41 of the remote control means 31. Specifically, the first internal pilot line 189 is connected at a first connection point 193 to the second internal connection line 177, which in turn is
10 connected to the second switching means 191 of the connection control device 29. Opening and closing of the second switching means 191, therefore, selectively supplies the hydraulic control fluid from one of the control output ports 39, 41 to the first internal pilot line 189 and the second internal connection line 177. By supplying sufficient pilot pressure via the first internal
15 pilot line 189, the first switching means 171, i.e. the on-off directional valve 183 is switched to its activated position 187 in which the second internal connection line 177 is connected to the third output port 137. Simultaneously, the first and second output ports 131, 133 are disconnected from the constant pressure hydraulic fluid of the auxiliary pump 63 as supplied from the first
20 input port 125. The second switching means 191, in this context, also forms part of the first connection control means 122 controlling the supply of hydraulic control fluid from the hydraulic remote control means 3 to the hydraulic adjustment means 77 of the variable displacement pump 51.

25 Specifically, the second switching means 191 comprises first and a second check valves 195, 197. The inlet side of the first and second check valves 195, 197, respectively, is connected in parallel to the first and second remote control lines 45, 47, in particular to their respective second line portions 147, 149 at second and third connection points 201, 203. The outlet side of the first
30 and second check valves 195, 197 is connected via a fourth connection point 205 to the second internal connection line 177 and thus also to the first internal pilot line 189.

The hydraulic remote control means 31 receives at the constant pressure inlet port 37 the constant pressure supplied from the sixth output port 159 of the connection control means 29 and modulates the same by means of the pressure variation means 35 between an initial control pressure and a maximum control pressure. The hydraulic fluid with the modulated pressure is directed to one of the first or second control output ports 39, 41 depending on the inclination of the control lever 33, the inclination direction of which indicating a desired mode of operation of the hydraulic transmission system, e.g. a "forward" or a "rearward" drive or rotation direction of a working implement such as the forward and rear rollers of a compactor. The modulating curve or characteristics of the pressure variation means 35 can be chosen as linear or non-linear, depending on the particular situation of application.

Once the control lever 33 is manipulated by the operator in either one of the directions indicating, for example, forward or rearward drive, a smooth modulated pressure signal is output from one of the first and second control output ports 39, 41 associated with the desired mode of operation. This modulated pressure signal is input into the connection control device 29 via one of the second and third input ports 143, 145 and operates selectively one of the first or second check valves 195, 197. As, under normal conditions, the hydraulic control fluid with sufficient pressure is only present in one of the second line portions 147, 149, and the other of the second line portions 147, 149 is depressurized, the respective one of the first or second check valves 195, 197 opens so as to communicate the hydraulic control fluid to the fourth connection point 205. The modulated pressure signal is then directed via the first connection point 193, 205 to the first internal pilot line 189 to position the on-off directional valve 183 in its activated position 187. The modulated pressure signal is also communicated via the fourth connection point 205 to the second internal connection line 177, and, in the activated position 187 of the on-off directional valve 183, it is directed via the fourth internal connection line 181 to the third output port 137 of the first control portion 121 of the connection control device 29.

The first switching means 171, when operated by manipulating the control lever 33 of the hydraulic remote control means 31 as described above, thus supplies the modulated pressure signal of the hydraulic remote control means 31 to the servo pressure inlet port 103 and the internal servo pressure supply line 99 of the supply means 3.

With further reference to Figs. 3 and 4 showing the first switching means 171 in the activated position 187, at the same time the modulated pressure is sent via one of the fourth and fifth output ports 151, 153 to the respective remote control input ports 43, 45 of the supply means 3 and pilots the directional distributor valve 91 into one of its first or second control positions 95, 97 so as to communicate the modulated pressure signal present on the internal servo pressure supply line 99 to one of the piston chambers of the servo piston 79.

Thus, the first connection control means 122 comprising the distributor means 89 and the first control portion 121 is operated by the hydraulic control fluid supplied from the hydraulic remote control means 31 and directs, upon actuation of the hydraulic remote control means 31, the hydraulic control fluid to the hydraulic adjustment means 77. In particular, when operating the hydraulic remote control means 31, initially only a slight movement of the directional distributor valve 91 is permitted. Also, because of the plug 101, the full charge pressure of the auxiliary pump 63 is not applied to the servo piston 79 at once, but instead it is supplied with hydraulic control fluid having the smoothly modulated pressure from the hydraulic remote control means 31 via the internal servo pressure supply line 99 and the servo pressure input port 103.

As mentioned above and with further reference to Fig. 1, besides the function provided by the first control portion 121 relating to the control of the adjustment means 77 of the variable displacement pump 51, the connection control device 29 also provides control of the connection of the first through fourth working line portions 21, 23, 25, 27 of the closed circuit hydraulic

system 1. In particular, the connection control device 29 comprises a second control portion 221 adapted to control the connection of the first through fourth working line portions 21, 23, 25, 27 so that the motors 13, 15 of the hydraulic system 1 can be selectively connected in series and/or in parallel.

5

As shown in more detail in Fig. 2, the second control portion 221 comprises first and second ports 231, 233 connected to the first and second working line portions 21, 23, respectively, and third and fourth ports 235, 237 connected to the third and fourth working line portions 25, 27, respectively. It further
10 comprises first and second internal working lines 241, 243 which are respectively connected to the first and second ports 231, 233, and third and fourth internal working lines 245, 247 connected respectively to the third and fourth ports 235, 237. There are also provided first and second branch lines 249, 251 of the first and second internal working lines 241, 243, respectively.

15

The first through fourth internal working lines 241, 243, 245, 247 and the first and second branch lines 249, 251 are connected to a third switching means 261 of the second control portion 221 adapted to controllably connect the internal working lines 241, 243, 245, 247 and the first and second branch lines
20 249, 251 in a selected manner.

Preferably, the third switching means 261 comprises a proportional 6-way directional valve 263 which is pilot operated by a pilot pressure provided on a second internal pilot line 265 into a position between a first extreme position
25 267 as shown in Figs. 1 and 2 and a second extreme position 269.

In the first extreme position 267 which may be also referred to as the neutral position of the proportional directional valve 263, the first and second internal working lines 241, 243 are connected and the third and fourth internal working
30 lines 245, 247 and the first and second branch lines 249, 251 are disconnected from each other so that effectively the first and second ports 231, 233 are connected with each other. Thus, with reference to Fig. 1, the first and second working line portions 21, 23 of the closed circuit are

connected with each other and provide for a serial connection of the first and second motors 13, 15, i.e. starting from the first supply port 5 via the first working line 9 to the first motor 13, the circuit of the hydraulic system 1 is closed via the second working line portion 23, second internal working line 243, first internal working line 241, first working line portion 21 to the second motor 15 and back to the second supply port 7 via the second working line 11.

In the second extreme position 269 of the third switching means 261, the first branch line 249 is connected to the third internal working line 245 and the second branch line 251 is connected to the fourth internal working line 247 so that effectively the first and the third ports 231, 235 are connected with one another and the second and the fourth ports 233, 237 are connected with one another. Thus, the first through fourth working line portions 21, 23, 25, 27 are connected with one another so as to provide a parallel connection of the first and second motors 13, 15 in the hydraulic system 1. In particular the first motor 13 is connected to the first and second supply ports 5, 7 of the supply means via the first working line 9 leading to the first motor 13, the second working line portion 23, the second internal working line portion 243 and its second branch line 251, the fourth internal working line portion 247 and the fourth working line portion 27 back to the second supply port 7. The second motor 15 is connected to the first supply port 5 via the first working line 9, the third working line portion 25, the third internal working line portion 245, the first internal working line portion 241 and its first branch line 249, the first working line portion 21 to the second motor 15 and back to the second supply port 7 via the second working line 11.

The pilot pressure to operate the third switching means 261 is provided via the second internal pilot line 265 which is also connected to the fourth connection point 205 receiving the modulated pressure of one of the first and second remote control lines 47, 49 through one of the first and second check valves 195, 197 of the second switching means 191 of the connection control device 29. In other words, the hydraulic transmission system 1 has a second connection control means 271 comprising the second switching means 191

and the second control portion 221 and responsive to a control signal, e.g. the hydraulic control fluid supplied from the hydraulic remote control means 31, so as to control the connection of the working line portions 21 to 25 selectively between a serial and a parallel connection.

5

The third switching means 261 is preferably proportional, e.g. it shifts from the first extreme position 267 to the second extreme position 269 proportional to the control signal, which is in the preferred case the pilot pressure applied through the second internal pilot line 265 to the proportional 6-way directional valve 263. This pilot pressure corresponds to the smoothly modulated pressure of the hydraulic control fluid from the hydraulic remote control means 31. Thus, the third switching means 261 provides a smooth change from series to parallel connection of the first and second motors 13, 15 in the hydraulic system 1. The lower the pilot pressure, the more the third switching means 261 is positioned towards the first extreme position 267.

15

A 6-way valve is preferred inasmuch in changing from the series configuration of the system 1 to the parallel configuration, the first and second working line portions 21, 23 having been connected in series are initially depressurized. This type of connection is less affected by forces when operating the proportional directional valve 263.

20

Figs. 3 and 4 show an intermediate state of the proportional 6-way directional valve 263 in which the connection configuration of the system 1 is transferred from series to parallel connection of the first and second motors 13, 15. It is illustrated that the higher the pilot pressure in the second pilot line 265, the more the connection between the first branch line 249 and the third internal working line 245 and the connection between the second branch line 251 and the fourth internal working line 247 are opened and the more the connection between the first and second internal working lines 241, 243 is closed.

25
30

The switching operation corresponds to opening and closing variable orifices of the proportional directional valve 263 and thus to proportional throttling

which allows a smooth change of the flow rate and the pressure during the transition from serial to parallel connection of the first and second motors 13, 15. If, for example, the pilot pressure signal on the second internal pilot line 265 ranges from 5 to 20 bar, the proportional directional valve 263 allows a first switching stage (e.g. in a range of 5 to 8 bar) during which the connection is almost series, and a second switching stage during which the first and second motors 13, 15 are connected in parallel.

Fig. 3 schematically represents the hydraulic system 1 in the intermediate condition. It shows that the modulated pressure of the hydraulic remote control means 31, e.g. from the second control output port 41 acting as pilot pressure on both the first and second internal pilot lines 189, 265 has effected also switching of the first switching means 171 to the activated position 187 so as to provide the same modulated pressure to the servo piston 79. The same modulated pressure from the second control output port 41 of the hydraulic remote control means 31 acts also as pilot pressure on the second distributor pilot line 107 of the distributor directional valve 91 and has moved the same into the first control position 95 so that the servo pressure corresponding to the modulated pressure on the servo pressure supply line 99 is supplied to a selected piston chamber of the servo piston 79 via the first servo piston control line 81.

The transition from serial to parallel connection is shown in a diagram as represented in Fig. 5 from which it can be seen that the behavior or change of the flow rate of the first and second motors 13, 15 during the transition from serial to parallel remains smooth. In the diagram of Fig. 5, the flow rate Q_{motor} of one of the motors 13, 15 is shown versus the pressure of the hydraulic control fluid as supplied from the hydraulic control means 31. Further, the variable flow rate of the displacement pump 51 is indicated by Q_{pump} . The maximum flow rate of the pump 51 is Q_{max} . With Q_{1max} and Q_{2max} indicating the maximum flow rates of the two motors 13 and 15, in the specifically shown embodiment of Fig. 5, the motors 13, 15 are of identical

construction and their respective maximum flow rates are the same, i.e. $Q1_{max} = Q2_{max}$.

During a first stage of operation of the hydraulic system 1, the flow rate Q_{motor} is equal or close to the flow rate Q_{pump} because of the predominantly serial connection configuration in which the flow rate of the whole hydraulic system 1 is constant. In a later stage with higher pressure of the hydraulic control fluid, in the parallel connection configuration the flow rate Q_{pump} is divided to the motors 13, 15 according to the loading. With equal loading on both motors, the flow rate Q_{pump} is equally partitioned to the motors 13, 15 so that Q_{motor} substantially corresponds to one half of Q_{pump} .

Although in the preferred embodiment the connection control device 29, i.e. the first and third switching means 171, 261, and also the directional distributor valve 91 are embodied as valves pilot operated by the hydraulic control fluid supplied by the hydraulic remote control means 31, it may be contemplated to provide a different control signal for the appropriate operation of the components of the connection control device 29 and the directional distributor valve 91. In particular, it may be envisaged to generate an electric signal indicative of the desired flow rate of the hydraulic working fluid, i.e. the operational speed of the system, which may be generated by sensing the inclination of the control lever 33, for example. Such a control signal can then be used to operate, for example by means of a solenoid, the respective switching valves. In particular, this offers an option in the case of the second connection control means 271 comprising the third switching means 261 which is provided to control the serial/parallel connection of the at least two motors 13, 15.

Although a major part of the first connection control means 122 and the second connection control means 271 are shown to be realized in one connection control device 29, it is to be noted that the second connection control means 271 controlling the connection configuration of the at least two motors 13, 15 can be realized independent from the first connection control

means 122 controlling the supply of hydraulic control fluid to the hydraulic adjustment means 77 of the variable displacement pump 51. By providing the second connection control means 271 independently from the first connection control means 122 the same advantages may be achieved as the connection of the at least two motors 13, 15 in the closed circuit hydraulic system 1 can be changed from serial to parallel configuration in response to a control signal, e.g. the pressure or flow rate of hydraulic working fluid supplied by the supply means 3.

10 Industrial applicability

According to one aspect, the hydraulic transmission system 1 is used in any closed circuit hydraulic system in which the supply means for hydraulic working fluid is connected to one or more users, as for example the motors 13, 15, in a closed circuit and in which the supply means is controlled by a hydraulic adjustment means. In hydraulic transmission systems of the prior art, no matter how fine the pressure modulation given by a pilot lever of a hydraulic remote control for operating the system, during the first instant of operation or movement of the system, one of the chambers of, for example, a servo piston of an axial piston pump receives the full charge pressure of the auxiliary pump causing a sudden flow peak of the hydraulic working fluid in the hydraulic transmission. This can result in undesirable consequences, for example if the hydraulic transmission system is used for driving an asphalt roller or compactor this may lead to a marking which is left in the asphalt surface by the compactor upon start. Such a drawback is avoided by the improved hydraulic transmission system 1 described herein, inasmuch upon actuation of the hydraulic remote control means 31 only a slight movement of the directional distributor valve 91 is permitted at the first instant of movement of the control lever 33.

30

As mentioned before, in hydraulic closed circuit transmission systems of the prior art the directional distributor valve is pilot operated in a standard manner to apply the full constant pressure of the auxiliary pump to the supply lines for

the hydraulic adjustment means 77. Fixed orifices are used downstream of the distributor valve to control the acceleration and deceleration ramp of the system. In such a situation it is very difficult to achieve a smooth regular ramp for the movement of a machine without using heavy duty or expensive electronics. Advantageously, the operation of the hydraulic adjustment means 77, e.g. the servo piston 79 of the variable displacement pump 51 of the hydraulic transmission system 1 of the present invention is ramped up in a controlled and smooth manner as the hydraulic control fluid having the control pressure which is supplied from the hydraulic remote control means 31 is applied to the chambers of the servo piston 79 directly.

In a typical hydraulic traction system for a utility machine, such as an asphalt roller having front and rear rollers driven by two hydraulic motors, the motors are connected in parallel to one supply means for hydraulic working fluid, e.g. a pump such as the variable displacement pump 51. The torque developed by parallel-connected motors is flow dependent and is affected by the shaft loading on each motor. If one of the motors is not shaft loaded it may receive all the flow and the torque value is very low. In an asphalt roller, for example, this may result in slippage on the front drum or roller when the compactor is ascending an inclined road surface with a low frictional coefficient. On the other hand, a series connection may result in over pressurization of the hydraulic circuit and cavitation of the motors.

According to another aspect of the invention, the at least two motors of, for example, a front and a rear roller of an asphalt compactor are initially connected in series. Upon start of the hydraulic transmission system 1, all of the motors are provided with sufficient hydraulic working fluid so as to initiate movement of the associated working implements, e.g. the asphalt front and rear rollers. Only after the working implements have reached a desired working condition, the connection configuration of the motors is transferred to a parallel configuration depending on the pressure of the hydraulic working fluid as indicated by the variable pressure of the hydraulic control fluid.

In the preferred embodiment as described above, both the control of the hydraulic adjustment means 77 of the supply means 3 and the control of the connection configuration of the at least two motors or users 13, 15 are achieved via one common control signal, e.g. the hydraulic control fluid
5 supplied by the hydraulic remote control means 31, which acts as the pilot signal for operating the first and second connection control means 122, 271 which comprise the first and second control portions 121, 221 of the connection control device 29 and the directional distributor valve 91. In addition, the same hydraulic control fluid is supplied to the hydraulic
10 adjustment means 77 of the variable displacement pump 51 to smoothly control the flow of the hydraulic working fluid in the hydraulic transmission system 1. Thus, in an effective and compact manner, both the change of the connection configuration from serial to parallel and the ramp of the pressure of the hydraulic working fluid are controlled by means of one control signal,
15 e.g. the hydraulic control fluid supplied by the hydraulic remote control means 31.

The invention as set forth above thus generally comprises features according to the following items which may be combined where appropriate and compatible:

5

1. According to a first aspect, a hydraulic transmission system comprises:

- supply means 3 adapted to supply a variable flow rate of hydraulic working fluid;
- said supply means 3 comprising hydraulic adjustment means 77 for
10 adjusting the variable flow rate of the hydraulic working fluid;
- actuatable hydraulic control means 31 having an actuated condition in which the actuatable hydraulic control means 31 generates a hydraulic control fluid having a control pressure which is adjustable between an initial control pressure and a maximum control pressure;
- 15 - first connection control means 122 operable by said hydraulic control fluid supplied from said hydraulic control means 31 and adapted to direct, upon actuation of said hydraulic control means 31, said hydraulic control fluid to said hydraulic adjustment means 77.

20 2. The hydraulic system 1 may further comprise:

- at least two working lines 9, 11 receiving said hydraulic working fluid at variable flow rate from said supply means 3;
- at least two hydraulic users 13, 15 connected to said supply means 3 via said at least two working lines 9, 11 in a closed circuit configuration;
- 25 - second connection control means 271 adapted to control the connection of working line portions 21, 23, 25, 27 connected to the at least two users 13, 15;
- said hydraulic control means 31 are adapted to generate a control signal indicative of a desired flow rate of the hydraulic working fluid supplied
30 by said supply means 3, and
- said second connection control means 271 are responsive to said control signal so as to selectively provide serial and/or parallel connection of

the at least two hydraulic users 13, 15 by selectively connecting the working line portions 21, 23, 25, 27.

3. The control signal may be the hydraulic control fluid with variable
5 pressure supplied by said hydraulic control means 31.

4. Said hydraulic control means 31 may have at least first and second control outputs 39, 41 supplying hydraulic control fluid and associated with respective first and second modes of operation of the hydraulic transmission
10 system.

5. Said first connection control means 122 may comprise distributor means 89 connected to said hydraulic adjustment means 77, said distributor means 89 has a control position 95, 97 in which it directs said hydraulic
15 control fluid to said hydraulic adjustment means 77 upon actuation of said hydraulic control means 31, said distributor means has further a neutral position 93 in which it connects the hydraulic adjustment means 77 to a hydraulic fluid tank 65.

20 6. Said distributor means 89 may comprise a pilot operated directional distributor valve 91 having a distributor pilot line 105, 107 connected to said hydraulic control fluid from the hydraulic control means 31 and being movable into said control position 95, 97 upon supply of said hydraulic control fluid on said distributor pilot line 105, 107 so as to selectively direct said hydraulic
25 control fluid from the hydraulic control means 31 to said hydraulic adjustment means 77.

7. Said first and second control outputs 39, 41 may be connected to first and second distributor pilot lines 105, 107 of the directional distributor valve
30 91 to move the distributor valve 91 in an associated first or second control position 95, 97, said hydraulic adjustment means 77 being responsive to the first or second control position 95, 97 so as to cause said supply means 3 to supply said hydraulic working fluid in a selected one of first and second flow

directions in the hydraulic system 1, said first and second flow directions being associated to said first and second control positions 95, 97.

8. Said first connection control means 122 may further comprise a first switching means 171 adapted to connect a supply line 99 of said distributor means 89 to the hydraulic control fluid from the hydraulic control means 31 in response to actuation of the hydraulic control means 31.

9. Said first switching means 171 may be adapted to connect said hydraulic adjustment means 77 to a supply of hydraulic fluid having constant pressure in the non activated condition of the hydraulic control means 31 and to disconnect said supply of hydraulic fluid having constant pressure from the hydraulic adjustment means 77 in the activated condition of the hydraulic control means 31.

10. Said first switching means 171 may be a pilot operated directional on-off valve 183 having an activated position 187 in which the directional on-off valve 183 directs said hydraulic control fluid from said hydraulic control means 31 to the distributor means 89.

11. Said directional on-off valve 183 further may have a neutral position 185 in which it connects said hydraulic adjustment means 77 to said supply of hydraulic fluid having constant pressure.

12. Said directional on-off valve 183 may have a first pilot line 189 selectively connectable to the hydraulic control fluid of the hydraulic control means 31, said directional on-off valve 183 being movable to its activated position 187 upon receiving hydraulic control fluid on said first pilot line 189.

13. Said hydraulic system 1 further may comprise second switching means 191 selectively connecting the first pilot line 189 of the directional on-off valve 183 to the first or second control outputs 39, 41 of the hydraulic control means 31.

14. Said second switching means 191 may comprise first and second check valves 195, 197 having their respective inputs connected to the first and second control outputs 39, 41 of the hydraulic control means 31 and having their respective outputs connected to the first pilot line 189 of the directional on-off valve 183.

15. Said second switching means 191 may selectively direct hydraulic control fluid of one of the first and second outputs 39, 41 of the hydraulic control means 31 to a control fluid input of the directional on-off valve 183, said control fluid input being connected to a control fluid output of the directional on-off valve 183 in its activated position 187.

16. Said supply means 3 may comprise a variable displacement pump 51 of the axial piston type with swash plate design and said hydraulic adjustment means 77 comprises a double acting servo piston 79 connected to said variable displacement pump 51.

17. In said control position 95, 97, said directional distributor valve 91 may direct said hydraulic control fluid from the hydraulic control means 31 to an associated one of the piston chambers of the servo piston 79.

18. Said directional distributor valve 91 may have a neutral position when no hydraulic control fluid is supplied to the distributor pilot line 105, 107, and wherein said neutral position of said directional distributor valve 91 connects both chambers of the servo piston to a tank 65 in order to balance the position of said servo piston 79.

19. Said hydraulic control means 31 may generate said hydraulic control fluid at continuously variable pressure between an initial control pressure and a maximum control pressure; wherein said second control means 271 is adapted to control the connection of the working line portions 21, 23, 25, 27 so as to change substantially smoothly from a serial connection configuration

at the initial control pressure to a parallel connection configuration at the maximum control pressure.

20. According to a second aspect, the hydraulic transmission system 1
5 comprises:

- supply means 3 adapted to supply hydraulic working fluid at variable pressure to at least two working lines 9, 11;

- at least two hydraulic users 13, 15 connected to said supply means 3 via said at least two working lines 9, 11 in a closed circuit configuration;

10 - control means 31 generating a control signal indicative of a desired flow rate of the hydraulic working fluid supplied by said supply means 3;

- second connection control means 271 responsive to said control signal adapted to control the connection of working line portions 21, 23, 25, 27 connected to the at least two users 13, 15 so as to selectively provide serial
15 and/or parallel connection of the at least two hydraulic users 13, 15 depending on said control signal.

21. Said control means 31 may be a hydraulic control means adapted to generate a hydraulic control fluid with varied pressure as said control signal.

20 22. The hydraulic system 1 may be configured such that:

- said supply means 3 comprises hydraulic adjustment means 77 for adjusting the variable pressure of the hydraulic working fluid;

- said hydraulic control means 31 having an actuated condition in which
25 the hydraulic control means 31 generates said hydraulic control fluid having a control pressure which is adjustable between an initial control pressure and a maximum control pressure;

- said hydraulic system 1 further comprises first connection control means 122 operable by said hydraulic control fluid supplied from said
30 hydraulic control means 31 and adapted to direct, upon actuation of said hydraulic control means 31, said hydraulic control fluid to said hydraulic adjustment means 77.

23. Said control means 31 may generate a continuously variable control signal between an initial control signal value and a maximum control signal value; wherein said second control means 271 is adapted to control the connection of the working line portions 21, 23, 25, 27 so as to change substantially smoothly from a serial connection configuration at the initial control signal value to a parallel connection configuration at the maximum control signal value.

24. Said second connection control means 271 may comprise a directional valve 263 having a first extreme position 267 in which it connects the working line portions 21, 23, 25, 27 in a serial connection configuration of the at least two users 13, 15 and having a second extreme position 269 in which it connects the working line portion 21, 23, 25, 27 in a parallel connection configuration of the at least two users 13, 15, said directional valve 263 being adapted to change its position responsive to the control signal.

25. Said directional valve 263 may be proportional and changes its position from the first extreme position 267 to the second extreme position 269 responsive and proportional to said control signal.

26. Said directional valve 263 may be a 6-way proportional valve adapted to depressurize the working line portions 21, 23 connected in a serial connection configuration when changing its position from the first extreme position 267 to the second extreme position 269.

27. Said directional valve 263 may be pilot operated by said hydraulic control fluid supplied by said hydraulic control means 31.

28. Said directional valve 263 may have a second pilot line 265 selectively connectable to the hydraulic control fluid of the hydraulic control means 31, said directional valve being movable from the first extreme position 267 towards the second extreme position 269 dependent on said varied pressure of said hydraulic control fluid.

29. Said hydraulic control means 31 may have at least first and second control outputs 39, 41 supplying hydraulic control fluid and associated with respective first and second modes; said first and second control outputs 39, 41 being selectively connectable to said second pilot line 265 of said directional valve 263.

30. Said hydraulic system 1 may further comprise second switching means 191 selectively connecting the second pilot line 265 of the directional valve 263 to the first or second control outputs 39, 41 of the hydraulic control means 31.

31. Said second switching means 191 may comprise first and second check valves 195, 197 having their respective inputs connected to the first and second control outputs 39, 41 of the hydraulic control means 31 and having their respective outputs connected to the second pilot line 265 of the directional valve 263.

32. In a method for controlling a hydraulic transmission system 1 comprising supply means 3 for supplying hydraulic working fluid at variable flow rate; wherein said supply means 3 comprising hydraulic adjustment means 77 for adjusting the variable flow rate of the hydraulic working fluid; said method comprises the steps of:

- providing a hydraulic control fluid having a control pressure which is adjustable between an initial control pressure and a maximum control pressure, said control pressure being indicative of a desired flow rate of the hydraulic working fluid;
- selectively directing said hydraulic control fluid during an actuated condition to said hydraulic adjustment means 77, and
- operating said hydraulic adjustment means 77 by means of said hydraulic control fluid.

33. In the method said actuated condition during which said hydraulic control fluid is selectively directed to said hydraulic adjustment means may correspond to providing said hydraulic control fluid with said initial pressure at minimum.

5

34. The method may further comprise, in a non-actuated condition, providing hydraulic fluid at constant pressure to said hydraulic adjustment means 77 and connecting the same to a tank 65 of hydraulic fluid.

10 35. Wherein said hydraulic transmission system 1 further comprises first connection control means 122 adapted to selectively direct said hydraulic control fluid to said hydraulic adjustment means, said method may comprise operating said first connection control means 122 by said hydraulic control fluid.

15

36. Wherein said supply means 3 are adapted to supply hydraulic working fluid at variable flow rate to at least two working lines 9, 11, and said hydraulic system 1 further comprises at least two hydraulic users 13, 15 connected to said supply means 3 via said at least two working lines 9, 11 in a closed circuit configuration; said method may further comprise the steps of:

20 - providing a control signal indicative of a desired flow rate of the hydraulic working fluid supplied by said supply means (3);
- controlling the connection of working line portions (21, 23, 25, 27) connected to the at least two users (13, 15) so as to selectively provide serial and/or parallel connection of the at least two hydraulic users (13, 15) in response to said control signal.

25

37. A Method of controlling a hydraulic transmission system 1 which comprises supply means 3 adapted to supply hydraulic working fluid at variable flow rate to at least two working lines 9, 11, and at least two hydraulic users 13, 15 connected to said supply means 3 via said at least two working lines 9, 11 in a closed circuit configuration; said method comprises the steps of:

30

- providing a control signal indicative of a desired flow rate of the hydraulic working fluid supplied by said supply means 3;
- controlling the connection of working line portions 21, 23, 25, 27 connected to the at least two users 13, 15 so as to selectively provide serial and/or parallel connection of the at least two hydraulic users 13, 15 in response to said control signal.

38. In the method said control signal may be provided continuously variable between an initial control signal value and a maximum control signal value; wherein said connection of the working line portions 21, 23, 25, 27 is controlled so as to change substantially smoothly from a serial connection configuration at the initial control signal value to a parallel connection configuration at the maximum control signal value.

39. In the method said connection of the working line portions 21, 23, 25, 27 may be controlled by second connection control means 271 which are operated by said control signal.

40. In the method said second connection control means 271 may be operable by a hydraulic pilot pressure, wherein said control signal is provided in the form of hydraulic control fluid having variable pressure corresponding to the desired pressure of the working fluid, said method further comprises the step of pilot operating said second connection control means 271 by said hydraulic control fluid.

41. In the method said supply means 3 may comprise hydraulic adjustment means 77 for adjusting the variable flow rate of the hydraulic working fluid; said method further comprises the steps of:

- providing a hydraulic control fluid having a control pressure which is adjustable between an initial control pressure and a maximum control pressure, said control pressure being indicative of a desired flow rate of the hydraulic working fluid;

- selectively directing said hydraulic control fluid during an actuated condition to said hydraulic adjustment means 77, and
- operating said hydraulic adjustment means 77 by means of said hydraulic control fluid.

Claims

1. Hydraulic transmission system (1) comprising:
 - 5 - supply means (3) adapted to supply a variable flow rate of hydraulic working fluid;
 - said supply means (3) comprising hydraulic adjustment means (77) for adjusting the variable flow rate of the hydraulic working fluid;
 - actuatable hydraulic control means (31) having an actuated condition in
10 which the actuatable hydraulic control means (31) generates a hydraulic control fluid having a control pressure which is adjustable between an initial control pressure and a maximum control pressure;
 - first connection control means (122) operable by said hydraulic control fluid supplied from said hydraulic control means (31) and adapted to direct,
15 upon actuation of said hydraulic control means (31), said hydraulic control fluid to said hydraulic adjustment means (77).
2. Hydraulic system (1) of claim 1, further comprising:
 - at least two working lines (9, 11) receiving said hydraulic working fluid
20 at variable flow rate from said supply means (3);
 - at least two hydraulic users (13, 15) connected to said supply means (3) via said at least two working lines (9, 11, 21, 23, 25, 27) in a closed circuit configuration;
 - second connection control means (271) adapted to control the
25 connection of working line portions (21, 23, 25, 27) connected to the at least two users (13, 15);
 - said hydraulic control means (31) are adapted to generate a control signal indicative of a desired flow rate of the hydraulic working fluid supplied by said supply means (3), and
30 - said second connection control means (271) are responsive to said control signal so as to selectively provide serial and/or parallel connection of the at least two hydraulic users (13, 15) by selectively connecting the working line portions (21, 23, 25, 27).

3. Hydraulic system (1) of claim 2, wherein said control signal is the hydraulic control fluid with variable pressure supplied by said hydraulic control means (31).

4. Hydraulic system (1) of one of the preceding claims, wherein said hydraulic control means (31) has at least first and second control outputs (39, 41) supplying hydraulic control fluid and associated with respective first and second modes of operation of the hydraulic transmission system.

5. Hydraulic system (1) of one of the preceding claims, wherein said first connection control means (122) comprises distributor means (89) connected to said hydraulic adjustment means (77), said distributor means (89) has a control position (95, 97) in which it directs said hydraulic control fluid to said hydraulic adjustment means (77) upon actuation of said hydraulic control means (31), said distributor means has further a neutral position (93) in which it connects the hydraulic adjustment means (77) to a hydraulic fluid tank (65);

wherein particularly said distributor means (89) comprise a pilot operated directional distributor valve (91) having a distributor pilot line (105, 107) connected to said hydraulic control fluid from the hydraulic control means (31) and being movable into said control position (95, 97) upon supply of said hydraulic control fluid on said distributor pilot line (105, 107) so as to selectively direct said hydraulic control fluid from the hydraulic control means (31) to said hydraulic adjustment means (77);

wherein particularly said first and second control outputs (39, 41) being connected to first and second distributor pilot lines (105, 107) of the directional distributor valve (91) to move the distributor valve (91) in an associated first or second control position (95, 97), said hydraulic adjustment means (77) being responsive to the first or second control position (95, 97) so as to cause said supply means (3) to supply said hydraulic working fluid in a selected one of first and second flow directions in the hydraulic system (1), said first and second flow directions being associated to said first and second control positions (95, 97);

wherein particularly said first connection control means (122) comprise a first switching means (171) adapted to connect a supply line (99) of said distributor means (89) to the hydraulic control fluid from the hydraulic control means (31) in response to actuation of the hydraulic control means (31);

5 wherein particularly said first switching means (171) is adapted to connect said hydraulic adjustment means (77) to a supply of hydraulic fluid having constant pressure in the non activated condition of the hydraulic control means (31) and to disconnect said supply of hydraulic fluid having constant pressure from the hydraulic adjustment means (77) in the activated condition
10 of the hydraulic control means (31);

wherein particularly said first switching means (171) is a pilot operated directional on-off valve (183) having an activated position (187) in which the directional on-off valve (183) directs said hydraulic control fluid from said hydraulic control means (31) to the distributor means (89);

15 wherein particularly said directional on-off valve (183) further has a neutral position (185) in which it connects said hydraulic adjustment means (77) to said supply of hydraulic fluid having constant pressure;

wherein particularly said directional on-off valve (183) has a first pilot line (189) selectively connectable to the hydraulic control fluid of the hydraulic control means (31), said directional on-off valve (183) being movable to its
20 activated position (187) upon receiving hydraulic control fluid on said first pilot line (189);

wherein particularly said hydraulic system (1) further comprises second switching means (191) selectively connecting the first pilot line (189) of the directional on-off valve (183) to the first or second control outputs (39, 41) of
25 the hydraulic control means (31);

wherein particularly said second switching means (191) comprises first and second check valves (195, 197) having their respective inputs connected to the first and second control outputs (39, 41) of the hydraulic control means
30 (31) and having their respective outputs connected to the first pilot line (189) of the directional on-off valve (183);

wherein particularly said second switching means (191) selectively directs hydraulic control fluid of one of the first and second outputs (39, 41) of

the hydraulic control means (31) to a control fluid input of the directional on-off valve (183), said control fluid input being connected to a control fluid output of the directional on-off valve (183) in its activated position (187).

5 6. Hydraulic system (1) of one of the preceding claims, wherein said supply means (3) comprise a variable displacement pump (51) of the axial piston type with swash plate design and said hydraulic adjustment means (77) comprises a double acting servo piston (79) connected to said variable displacement pump (51);

10 wherein particularly, in said control position (95, 97), said directional distributor valve (91) directs said hydraulic control fluid from the hydraulic control means (31) to an associated one of the piston chambers of the servo piston (79);

15 wherein particularly said directional distributor valve (91) has a neutral position when no hydraulic control fluid is supplied to the distributor pilot line (105, 107), and wherein said neutral position of said directional distributor valve (91) connects both chambers of the servo piston to a tank (65) in order to balance the position of said servo piston (79).

20 7. Hydraulic system (1) of one of the claims 3 to 6, wherein said hydraulic control means (31) generates said hydraulic control fluid at continuously variable pressure between an initial control pressure and a maximum control pressure; wherein said second control means (271) is adapted to control the connection of the working line portions (21, 23, 25, 27) so as to change
25 substantially smoothly from a serial connection configuration at the initial control pressure to a parallel connection configuration at the maximum control pressure.

30 8. Hydraulic system (1) of one of the claims 2 to 7, wherein said second connection control means (271) comprises a directional valve (263) having a first extreme position (267) in which it connects the working line portions (21, 23, 25, 27) in a serial connection configuration of the at least two users (13, 15) and having a second extreme position (269) in which it connects the

working line portion (21, 23, 25, 27) in a parallel connection configuration of the at least two users (13, 15), said directional valve (263) being adapted to change its position responsive to the control signal;

5 wherein particularly said directional valve (263) is proportional and changes its position from the first extreme position (267) to the second extreme position (269) responsive and proportional to said control signal;

10 wherein particularly said directional valve (263) is a 6-way proportional valve adapted to depressurize the working line portions (21, 23) connected in a serial connection configuration when changing its position from the first extreme position (267) to the second extreme position (269);

wherein particularly said directional valve (263) is pilot operated by said hydraulic control fluid supplied by said hydraulic control means (31);

15 wherein particularly said directional valve (263) has a second pilot line (265) selectively connectable to the hydraulic control fluid of the hydraulic control means (31), said directional valve being movable from the first extreme position (267) towards the second extreme position (269) dependent on said varied pressure of said hydraulic control fluid;

20 wherein particularly said first and second control outputs (39, 41) of said hydraulic control means (31) are selectively connectable to said second pilot line (265) of said directional valve (263);

25 wherein particularly said second switching means (191) of said hydraulic system also are adapted to selectively connect the second pilot line (265) of the directional valve (263) to the first or second control outputs (39, 41) of the hydraulic control means (31);

30 wherein particularly said second switching means (191) comprises first and second check valves (195, 197) having their respective inputs connected to the first and second control outputs (39, 41) of the hydraulic control means (31) and having their respective outputs connected to the second pilot line (265) of the directional valve (263).

9. Hydraulic transmission system (1) comprising:

- supply means (3) adapted to supply hydraulic working fluid at variable pressure to at least two working lines (9, 11);

- at least two hydraulic users (13, 15) connected to said supply means (3) via said at least two working lines (9, 11) in a closed circuit configuration;
- control means (31) generating a control signal indicative of a desired flow rate of the hydraulic working fluid supplied by said supply means (3);
- 5 - second connection control means (271) responsive to said control signal adapted to control the connection of working line portions (21, 23, 25, 27) connected to the at least two users (13, 15) so as to selectively provide serial and/or parallel connection of the at least two hydraulic users (13, 15) depending on said control signal.

10

10. Hydraulic system (1) of claim 9, wherein said control means (31) is a hydraulic control means adapted to generate a hydraulic control fluid with varied pressure as said control signal.

15 11. Hydraulic system (1) of claim 10, wherein:

- said supply means (3) comprises hydraulic adjustment means (77) for adjusting the variable pressure of the hydraulic working fluid;
- said hydraulic control means (31) having an actuated condition in which the hydraulic control means (31) generates said hydraulic control fluid having
- 20 a control pressure which is adjustable between an initial control pressure and a maximum control pressure;
- said hydraulic system (1) further comprises first connection control means (122) operable by said hydraulic control fluid supplied from said hydraulic control means (31) and adapted to direct, upon actuation of said
- 25 hydraulic control means (31), said hydraulic control fluid to said hydraulic adjustment means (77).

12. Hydraulic system (1) of claim 9 or 10, wherein said control means (31) generates a continuously variable control signal between an initial control

30 signal value and a maximum control signal value; wherein said second control means (271) is adapted to control the connection of the working line portions (21, 23, 25, 27) so as to change substantially smoothly from a serial

connection configuration at the initial control signal value to a parallel connection configuration at the maximum control signal value.

13. Hydraulic system (1) of one of the claims 9 to 12, wherein said second
5 connection control means (271) comprises a directional valve (263) having a first extreme position (267) in which it connects the working line portions (21, 23, 25, 27) in a serial connection configuration of the at least two users (13, 15) and having a second extreme position (269) in which it connects the working line portion (21, 23, 25, 27) in a parallel connection configuration of
10 the at least two users (13, 15), said directional valve (263) being adapted to change its position responsive to the control signal;

wherein particularly said directional valve (263) is proportional and changes its position from the first extreme position (267) to the second extreme position (269) responsive and proportional to said control signal;

15 wherein particularly said directional valve (263) is a 6-way proportional valve adapted to depressurize the working line portions (21, 23) connected in a serial connection configuration when changing its position from the first extreme position (267) to the second extreme position (269);

wherein particularly said directional valve (263) is pilot operated by said
20 hydraulic control fluid supplied by said hydraulic control means (31);

wherein particularly said directional valve (263) has a second pilot line (265) selectively connectable to the hydraulic control fluid of the hydraulic control means (31), said directional valve being movable from the first extreme position (267) towards the second extreme position (269) dependent on said
25 varied pressure of said hydraulic control fluid;

wherein particularly said hydraulic control means (31) has at least first and second control outputs (39, 41) supplying hydraulic control fluid and associated with respective first and second modes; said first and second control outputs (39, 41) being selectively connectable to said second pilot line
30 (265) of said directional valve (263);

wherein particularly said hydraulic system (1) further comprises second switching means (191) selectively connecting the second pilot line (265) of the

directional valve (263) to the first or second control outputs (39, 41) of the hydraulic control means (31);

wherein particularly said second switching means (191) comprises first and second check valves (195, 197) having their respective inputs connected to the first and second control outputs (39, 41) of the hydraulic control means (31) and having their respective outputs connected to the second pilot line (265) of the directional valve (263);

14. Hydraulic system (1) of one of the claims 11 to 13, wherein said first connection control means (122) comprises distributor means (89) connected to said hydraulic adjustment means (77), said distributor means (89) has a control position (95, 97) in which it directs said hydraulic control fluid to said hydraulic adjustment means (77) upon actuation of said hydraulic control means (31), said distributor means has further a neutral position (93) in which it connects the hydraulic adjustment means (77) to a hydraulic fluid tank (65);

wherein particularly said distributor means (89) comprise a pilot operated directional distributor valve (91) having a distributor pilot line (105, 107) connected to said hydraulic control fluid from the hydraulic control means (31) and being movable into said control position (95, 97) upon supply of said hydraulic control fluid on said distributor pilot line (105, 107) so as to selectively direct said hydraulic control fluid from the hydraulic control means (31) to said hydraulic adjustment means (77);

wherein particularly said first and second control outputs (39, 41) of said hydraulic control means (31) are connected to first and second distributor pilot lines (105, 107) of the directional distributor valve (91) to move the distributor valve (91) in an associated first or second control position (95, 97), said hydraulic adjustment means (77) being responsive to the first or second control position (95, 97) so as to cause said supply means (3) to supply said hydraulic working fluid in a selected one of first and second flow directions in the hydraulic system (1), said first and second flow directions being associated to said first and second control positions (95, 97);

wherein particularly said first connection control means (122) comprise a first switching means (171) adapted to connect a supply line (99) of said

distributor means (89) to the hydraulic control fluid from the hydraulic control means (31) in response to actuation of the hydraulic control means (31);

wherein particularly said first switching means (171) is adapted to connect said hydraulic adjustment means (77) to a supply of hydraulic fluid having constant pressure in the non activated condition of the hydraulic control means (31) and to disconnect said supply of hydraulic fluid having constant pressure from the hydraulic adjustment means (77) in the activated condition of the hydraulic control means (31);

wherein particularly said first switching means (171) is a pilot operated directional on-off valve (183) having an activated position (187) in which the directional on-off valve (183) directs said hydraulic control fluid from said hydraulic control means (31) to the distributor means (89);

wherein particularly said directional on-off valve (183) further has a neutral position (185) in which it connects said hydraulic adjustment means (77) to said supply of hydraulic fluid having constant pressure;

wherein particularly said directional on-off valve (183) has a first pilot line (189) selectively connectable to the hydraulic control fluid of the hydraulic control means (31), said directional on-off valve (183) being movable to its activated position (187) upon receiving hydraulic control fluid on said first pilot line (189);

wherein particularly said second switching means (191) of said hydraulic system (1) selectively connects the first pilot line (189) of the directional on-off valve (183) to the first or second control outputs (39, 41) of the hydraulic control means (31);

wherein particularly said second switching means (191) comprises first and second check valves (195, 197) having their respective inputs connected to the first and second control outputs (39, 41) of the hydraulic control means (31) and having their respective outputs connected to the first pilot line (189) of the directional on-off valve (183);

wherein particularly said second switching means (191) selectively directs hydraulic control fluid of one of the first and second outputs (39, 41) of the hydraulic control means (31) to a control fluid input of the directional on-off

valve (183), said control fluid input being connected to a control fluid output of the directional on-off valve (183) in its activated position (187).

15. Hydraulic system (1) of one of the preceding claims 11 to 14, wherein
5 said supply means (3) comprise a variable displacement pump (51) of the axial piston type with swash plate design and said hydraulic adjustment means (77) comprises a double acting servo piston (79) connected to said variable displacement pump (51);

wherein particularly, in said control position (95, 97), said directional
10 distributor valve (91) directs said hydraulic control fluid from the hydraulic control means (31) to an associated one of the piston chambers of the servo piston (79);

wherein particularly said directional distributor valve (91) has a neutral position when no hydraulic control fluid is supplied to the pilot line (105, 107),
15 and wherein said neutral position of said directional distributor valve (91) connects both chambers of the servo piston to a tank (65) in order to balance the position of said servo piston (79).

16. Method for controlling a hydraulic transmission system (1), said
20 hydraulic transmission system (1) comprising supply means (3) for supplying hydraulic working fluid at variable flow rate; wherein said supply means (3) comprising hydraulic adjustment means (77) for adjusting the variable flow rate of the hydraulic working fluid;

said method comprises the steps of:

25 - providing a hydraulic control fluid having a control pressure which is adjustable between an initial control pressure and a maximum control pressure, said control pressure being indicative of a desired flow rate of the hydraulic working fluid;

- selectively directing said hydraulic control fluid during an actuated
30 condition to said hydraulic adjustment means (77), and

- operating said hydraulic adjustment means (77) by means of said hydraulic control fluid.

17. Method of claim 16 wherein said actuated condition during which said hydraulic control fluid is selectively directed to said hydraulic adjustment means corresponds to providing said hydraulic control fluid with said initial pressure at minimum;

5 said method further comprising particularly, in a non-actuated condition, providing hydraulic fluid at constant pressure to said hydraulic adjustment means (77) and connecting the same to a tank (65) of hydraulic fluid.

18. Method of one of the claims 16 or 17, wherein said hydraulic
10 transmission system (1) further comprises first connection control means (122) adapted to selectively direct said hydraulic control fluid to said hydraulic adjustment means, said method comprises the step of operating said first connection control means (122) by said hydraulic control fluid.

15 19. Method of one of the claims 16 to 18, wherein said supply means (3) are adapted to supply hydraulic working fluid at variable flow rate to at least two working lines (9, 11), and said hydraulic system (1) further comprises at least two hydraulic users (13, 15) connected to said supply means (3) via said at least two working lines (9, 11) in a closed circuit configuration; said method
20 further comprises the steps of:

- providing a control signal indicative of a desired flow rate of the hydraulic working fluid supplied by said supply means (3);
- controlling the connection of working line portions (21, 23, 25, 27) connected to the at least two users (13, 15) so as to selectively provide serial
25 and/or parallel connection of the at least two hydraulic users (13, 15) in response to said control signal;

wherein particularly said control signal is provided continuously variable between an initial control signal value and a maximum control signal value; wherein said connection of the working line portions (21, 23, 25, 27) is
30 controlled so as to change substantially smoothly from a serial connection configuration at the initial control signal value to a parallel connection configuration at the maximum control signal value;

wherein particularly said connection of the working line portions (21, 23, 25, 27) is controlled by second connection control means (271) which are operated by said control signal;

wherein particularly said second connection control means (271) are operable by a hydraulic pilot pressure, wherein said control signal is provided in the form of said hydraulic control fluid having variable pressure corresponding to the desired pressure of the working fluid, said method further comprises the step of pilot operating said second connection control means (271) by said hydraulic control fluid.

10

20. Method of controlling a hydraulic transmission system (1) which comprises supply means (3) adapted to supply hydraulic working fluid at variable flow rate to at least two working lines (9, 11), and at least two hydraulic users (13, 15) connected to said supply means (3) via said at least two working lines (9, 11) in a closed circuit configuration; said method comprises the steps of:

15

- providing a control signal indicative of a desired flow rate of the hydraulic working fluid supplied by said supply means (3);
- controlling the connection of working line portions (21, 23, 25, 27) connected to the at least two users (13, 15) so as to selectively provide serial and/or parallel connection of the at least two hydraulic users (13, 15) in response to said control signal.

20

21. Method of claim 20, wherein said control signal is provided continuously variable between an initial control signal value and a maximum control signal value; wherein said connection of the working line portions (21, 23, 25, 27) is controlled so as to change substantially smoothly from a serial connection configuration at the initial control signal value to a parallel connection configuration at the maximum control signal value.

25
30

22. Method of claim 20 or 21, wherein said connection of the working line portions (21, 23, 25, 27) is controlled by second connection control means (271) which are operated by said control signal;

wherein particularly said second connection control means (271) are operable by a hydraulic pilot pressure, wherein said control signal is provided in the form of hydraulic control fluid having variable pressure corresponding to the desired pressure of the working fluid, said method further comprises the step of pilot operating said second connection control means (271) by said hydraulic control fluid.

23. Method of one of the claims 20 to 22, wherein said supply means (3) comprising hydraulic adjustment means (77) for adjusting the variable flow rate of the hydraulic working fluid;

said method further comprises the steps of:

- providing a hydraulic control fluid having a control pressure which is adjustable between an initial control pressure and a maximum control pressure, said control pressure being indicative of a desired flow rate of the hydraulic working fluid;
- selectively directing said hydraulic control fluid during an actuated condition to said hydraulic adjustment means (77), and
- operating said hydraulic adjustment means (77) by means of said hydraulic control fluid;

wherein particularly said actuated condition during which said hydraulic control fluid is selectively directed to said hydraulic adjustment means corresponds to providing said hydraulic control fluid with said initial pressure at minimum;

said method further comprising particularly, in a non-actuated condition, providing hydraulic fluid at constant pressure to said hydraulic adjustment means (77) and connecting the same to a tank (65) of hydraulic fluid;

wherein particularly said hydraulic transmission system (1) further comprises first connection control means (122) adapted to selectively direct said hydraulic control fluid to said hydraulic adjustment means, said method comprises operating said first connection control means (122) by said hydraulic control fluid.

Abstract

According to the present invention an improved hydraulic transmission system
5 is provide which comprises: supply means adapted to supply a variable flow
rate of hydraulic working fluid, said supply means comprising hydraulic
adjustment means for adjusting the variable flow rate of the hydraulic working
fluid; actuatable hydraulic control means having an actuated condition in
10 which the actuatable hydraulic control means generates a hydraulic control
fluid having a control pressure which is adjustable between an initial control
pressure and a maximum control pressure; and first connection control means
operable by said hydraulic control fluid supplied from said hydraulic control
means and adapted to direct, upon actuation of said hydraulic control means,
said hydraulic control fluid to said hydraulic adjustment means.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5